

HARDWARE SPECIFICATIONS

Processor

VIA Eden 1 GHz

Operating Systems

Windows XP Embedded

Cache

On Die 1 MB

Memory

768 MB

Touchscreen

Industrial resistive

Storage

40 GB HDD with shock damper

Display

10.4" XGA sunlight readable

Wireless

Internal 802.11 a/b/g with integrated antenna

Bluetooth Class2, v2.0+EDR with integrated antenna

GPS

Internal GPS with integrated antenna

Audio

CX700M built-in audio with high definition external CODEC

Battery

Rechargeable Li-Ion Smart Battery, 10.8v, 4800 mAh 3S2P

Power Adaptor

Universal AC 90V-265V, 47-63Hz input; 19V, 3.16A output

Application Buttons

1 Power Button

12 Numeric Keys

1 Software Keyboard Button

4 Programmable Function Buttons

4-Way navigation button w/integrated Enter button

I/O Interfaces

2 USB 2.0

2 RS232/422/485 Ports

1 VGA output

1 CF Type II slot

1 PCMCIA Type II Slot

1 internal mono mic

1 internal stereo speaker

1 RJ45 for 10/100/1Gb Ethernet

1 RJ11 for 56 kbps v.92/k56 flex modem

1 Stereo Headphone Jack

1 Microphone Jack

1 DC-in Jack

1 Docking Connector

Accessories (available at additional cost)

External Keyboard

Vehicle and Fixed Mount Docking Stations

Hand and Shoulder Strap

4-Slot External Battery Charger

Physical

12.21W x 9.29H x 1.65D

Ridgeline Tablet



ENVIRONMENTAL SPECIFICATIONS

Environment

Operating Temperature -20 to +60C

Storage Temperature -40 to +70C

Operating Humidity 5% - 95%

Rugged Specification

IP65 Sealing

3 foot drop to concrete

Mil-STD-810F

MIL-STD-461E

Certification

CE, FCC, cUL/UL, TUV, VCCI, ETL, Semko, C-Tick

Specifications subject to change

Hardware in partnership with

Glacier Computer, LLC